**♦** INTERNATIONAL

September 24, 2025

Prepared For: City of Lee's Summit Mark Stinson 207 S.W. Market Lee's Summit, MO 64063-(816)969 - 1061

Reference ID: service body

Presented By:
RUSH TRK CTR OF MO
Howard J Gentry
7700 NE 38TH ST.
KANSAS CITY MO 641619456
816-455-1833

# Model Profile 2026 MV607 SBA (MV607)

AXLE CONFIG: 4X2

APPLICATION: Service Body

MISSION: Requested GVWR: 33000. Calc. GVWR: 36220. Calc. GCWR: 80000

Calc. Start / Grade Ability: 41.08% / 2.26% @ 55 MPH

Calc. Geared Speed: 84.6 MPH

**DIMENSION:** Wheelbase: 191.00, CA: 123.90, Axle to Frame: 75.00

**ENGINE, DIESEL:** {Cummins L9 300} EPA 2024, 300HP @ 2200 RPM, 860 lb-ft Torque @ 1200 RPM, 2200 RPM

Governed Speed, 300 Peak HP (Max)

TRANSMISSION, AUTOMATIC: {Allison 3500 RDS} 6th Generation Controls, Wide Ratio, 6-Speed with Double Overdrive, with

PTO Provision, Less Retarder, Includes Oil Level Sensor, with 80,000-lb GVW and GCW Max,

On/Off Highway

CLUTCH: Omit Item (Clutch & Control)

AXLE, FRONT NON-DRIVING: {Meritor MFS-14-122A} I-Beam Type, 14,000-lb Capacity

AXLE, REAR, SINGLE: {Meritor RS-23-160} Single Reduction, 23,000-lb Capacity, 200 Wheel Ends Gear Ratio: 4.89

1

CAB: Conventional, Day Cab

TIRE, FRONT:
(3) 11R22.5 Load Range H HSR 3 (CONTINENTAL), 494 rev/mile, 75 MPH, All-Position
TIRE, REAR:
(4) 11R22.5 Load Range H HDR2+ (CONTINENTAL), 491 rev/mile, 75 MPH, Drive
SUSPENSION, REAR, SINGLE:
23,500-lb Capacity, Vari-Rate Springs, with 4500-lb Capacity Auxiliary Rubber Springs

PAINT: Cab schematic 100WP

Location 1: 9219, Winter White (Std)

Chassis schematic N/A

## Vehicle Specifications 2026 MV607 SBA (MV607)

## **Description**

Base Chassis, Model MV607 SBA with 191.00 Wheelbase, 123.90 CA, and 75.00 Axle to Frame.

TOW HOOK, FRONT (2) Frame Mounted

**AXLE CONFIGURATION 4x2** 

FRAME RAILS Heat Treated Alloy Steel (120,000 PSI Yield); 10.250" x 3.610" x 0.375" (260.4mm x 91.7mm x 9.5mm); 456.0" (11582mm) Maximum OAL

LICENSE PLATE HOLDER Includes Upper & Lower Mounting Plate Hardware, Mounted in Existing Holes in Front Bumper

BUMPER, FRONT Contoured, Steel, Painted Gloss Black

WHEELBASE RANGE 134" (340cm) Through and Including 197" (500cm)

AXLE, FRONT NON-DRIVING (Meritor MFS-14-122A) I-Beam Type, 14,000-lb Capacity

SUSPENSION, FRONT, SPRING Parabolic Taper Leaf, Shackle Type, 14,000-lb Capacity, with Shock Absorbers

BRAKE SYSTEM, AIR Dual System for Straight Truck Applications

TRAILER CONNECTIONS Four-Wheel, with Hand Control Valve and Tractor Protection Valve, for Straight Truck

DRAIN VALVE (Berg) with Pull Chain, for Air Tank

AIR BRAKE ABS (Bendix AntiLock Brake System) 4-Channel (4 Sensor/4 Modulator) Full Vehicle Wheel Control System

AIR DRYER {Wabco HP} with Heater

BRAKE CHAMBERS, REAR AXLE (Bendix EverSure) 30/30 Sqln Spring Brake

BRAKE CHAMBERS, FRONT AXLE (Bendix) 24 SqIn

BRAKE, PARKING Manual Push-Pull Pneumatic Parking Brake

SLACK ADJUSTERS, FRONT (Haldex) Automatic

SLACK ADJUSTERS, REAR {Haldex} Automatic

AIR COMPRESSOR (Cummins) 18.7 CFM

AIR DRYER LOCATION Mounted Inside Engine Compartment, Right Side

DUST SHIELDS, FRONT BRAKE for Air Cam Brakes

DUST SHIELDS, REAR BRAKE for Air Cam Brakes

BRAKES, FRONT (Meritor 16.5X5 Q-PLUS CAST) Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 5", 14,700-lb Capacity

BRAKES, REAR {Meritor 16.5X7 Q-PLUS CAST} Air S-Cam Type, Cast Spider, Fabricated Shoe, Double Anchor Pin, Size 16.5" X 7", 23,000-lb Capacity per Axle

AIR TANK LOCATION (2) Mounted Between the Rails, Back of Cab, One on Each Side, Parallel to Rails

STEERING COLUMN Tilting

STEERING WHEEL 4-Spoke; 18" Dia., Black

STEERING GEAR (Sheppard M100) Power

DRIVELINE SYSTEM (Dana Spicer) 1710, for 4x2/6x2

AFTERTREATMENT COVER Aluminum

EXHAUST SYSTEM Horizontal Aftertreatment System, Frame Mounted Right Side Under Cab, for Single Vertical Tail Pipe, Frame Mounted Right Side Back of Cab

ENGINE EXHAUST BRAKE for Cummins ISB/B6.7/ISL/L9 Engine with Variable Vane Turbo Charger

## **Description**

TAIL PIPE (1) Turnback Type

**EXHAUST HEIGHT 10'** 

MUFFLER/TAIL PIPE GUARD (1) Aluminum

SWITCH, FOR EXHAUST 2 Position, Lighted & Latching, On/Off Type, Mounted in IP, Inhibits Diesel Particulate Filter Regeneration as Long as Switch is in On Position

ELECTRICAL SYSTEM 12-Volt, Standard Equipment

CIGAR LIGHTER Includes Ash Cup

ALTERNATOR {Leece-Neville AVI160P2013} Brush Type, 12 Volt, 160 Amp Capacity, Pad Mount, with Remote Sense

BODY BUILDER WIRING Back of Day Cab at Left Frame or Under Sleeper, Extended or Crew Cab at Left Frame; Includes Sealed Connectors for Tail/Amber Turn/Marker/ Backup/Accessory Power/Ground and Sealed Connector for Stop/Turn

ELECTRIC TRAILER BRAKE/LIGHTS Accommodation Package to Rear of Frame; for Combined Trailer Stop, Tail, Turn, Marker Light Circuits; Includes Electric Trailer Brake Accommodation Package with Cab Connections for Mounting Customer Installed Electric Brake Unit, Less Trailer Socket

BATTERY SYSTEM (Fleetrite) Maintenance-Free, (3) 12-Volt 1980CCA Total, Top Threaded Stud

TAIL LIGHT WIRING MODIFIED Includes: Wiring for Standard Lt & Rt Tail Lights; Separate 8.0' of Extra Cable Wiring for Lt & Rt Body Mounted Tail Lights

SPEAKERS (2) 6.5" Dual Cone Mounted in Doors

ANTENNA for Increased Roof Clearance Applications

RADIO AM/FM/WB/Clock/USB Input/Auxiliary Input

TRAILER AUXILIARY FEED CIRCUIT for Electric Trailer Brake Accommodation/Air Trailer ABS; with 30 Amp Fuse and Relay, Controlled by Ignition Switch

BATTERY CABLES with 1 Auxiliary Battery Post, Positive

HORN, ELECTRIC (1) Trumpet Style

JUMP START STUD 12V, Remote Mounted

WINDSHIELD WIPER SPD CONTROL Force Wipers to Slowest Intermittent Speed When Park Brake Set and Wipers Left on for a Predetermined Time

CLEARANCE/MARKER LIGHTS (5) {Truck Lite} Amber LED Lights, Flush Mounted on Cab or Sunshade

TEST EXTERIOR LIGHTS Pre-Trip Inspection will Cycle all Exterior Lamps Except Back-up Lights

HEADLIGHTS ON W/WIPERS Headlights Will Automatically Turn On if Windshield Wipers are Turned On

INDICATOR, LOW COOLANT LEVEL with Audible Alarm

ALARM, PARKING BRAKE Electric Horn Sounds in Repetitive Manner When Vehicle Park Brake is "NOT" Set, with Ignition "OFF" and any Door Opened

STARTING MOTOR (Mitsubishi Electric Automotive America 105P) 12-Volt, with Soft-Start

CIRCUIT BREAKERS Manual-Reset (Main Panel) SAE Type III with Trip Indicators, Replaces All Fuses

BATTERY BOX Steel, with Aluminum Cover, 14" Wide, 2-3 Battery Capacity, Mounted Left Side Under Cab

BATTERY DISCONNECT SWITCH 300 Amp, Disconnects Charging Circuits, Locks with Padlock, Cab Mounted

HORN, AIR Single Trumpet, Black, with Lanyard Pull Cord

ALARM, PARK BRAKE, TIMER Programmable Parameter to Change Alarm Trigger Time

## **Description**

**HEADLIGHTS Halogen** 

USB PORT One USB-A Port and One USB-C Port, Located in Instrument Panel

LOGOS EXTERIOR Model Badges

LOGOS EXTERIOR, ENGINE Badges

**GRILLE Molded in Black** 

FENDER EXTENSIONS Painted

FRONT END Tilting, Fiberglass, with Three Piece Construction, Dual Air Intakes

BUG SCREEN Mounted Behind Grille and Bumper Grille

PAINT SCHEMATIC, PT-1 Single Color, Design 100

PAINT TYPE Base Coat/Clear Coat, 1-2 Tone

COMMUNICATIONS MODULE Telematics Device with Over the Air Programming; Includes Five Year Data Plan and International 360

PROMOTIONAL PACKAGE Government Silver Package

VEHICLE REGISTRATION IDENTITY ID for Non-CARB Omnibus and/or Non-ACT Adopting State or Exempt Vehicle. Not for use on vehicles registering in CA/MA /OR/NJ/NY/WA. Contains non-mitigated legacy engine & cannot be registered in CA unless exempt. You may be held liable under state law for failure to properly register vehicle.

MUD FLAPS, FRONT WHEELS (2) Rubber, Mounted on Fender Extension

CLUTCH Omit Item (Clutch & Control)

ANTI-FREEZE Red, Extended Life Coolant; To -40 Degrees F/ -40 Degrees C, Freeze Protection

BLOCK HEATER, ENGINE 120V/1000W, for Cummins ISB/B6.7/ISL/L9 Engines

ENGINE, DIESEL (Cummins L9 300) EPA 2024, 300HP @ 2200 RPM, 860 lb-ft Torque @ 1200 RPM, 2200 RPM Governed Speed, 300 Peak HP (Max)

FAN DRIVE (Horton Drivemaster) Automatic On/Off Type, with Normally Closed Temperature Control

AIR CLEANER Single Element, Fire Retardant Media

EMISSION, CALENDAR YEAR {Cummins L9} EPA, OBD and GHG Certified for Calendar Year 2025

THROTTLE, HAND CONTROL Engine Speed Control for PTO; Electronic, Stationary Pre-Set, Two Speed Settings; Mounted on Steering Wheel

EPA IDLE COMPLIANCE Low NOx Idle Engine, Complies with EPA Clean Air Regulations; Includes "Certified Clean Idle" Decal on Hood

CARB IDLE COMPLIANCE Does Not Comply with California Clean Air Idle Regulations

ENGINE CONTROL, REMOTE MOUNTED Provision for; Includes Wiring for Body Builder Installation of PTO Controls and Starter Lockout, with Ignition Switch Control, for Cummins B6.7 and L9 Engines

RADIATOR Aluminum, 3-Row, Down Flow, Front to Back System, 837 Sqln Louvered, with 477 Sqln Charge Air Cooler, Includes In-Tank Oil Cooler

CARB EMISSION WARR COMPLIANCE Does Not Comply with CARB Emission Warranty

TRANSMISSION, AUTOMATIC (Allison 3500 RDS) 6th Generation Controls, Wide Ratio, 6-Speed with Double Overdrive, with PTO Provision, Less Retarder, Includes Oil Level Sensor, with 80,000-lb GVW and GCW Max, On/Off Highway

TRANSMISSION SHIFT CONTROL Column Mounted Stalk Shifter, Not for Use with Allison 1000 & 2000 Series Transmission

TRANSMISSION DIPSTICK Relocated to Right Side of Transmission

TRANSMISSION OIL Synthetic; 29 thru 42 Pints

## Vehicle Specifications 2026 MV607 SBA (MV607)

## **Description**

ALLISON SPARE INPUT/OUTPUT for Rugged Duty Series (RDS) and Regional Haul Series (RHS), General Purpose Trucks, Construction, Package Number 223

NEUTRAL AT STOP Allison Transmission Shifts to Neutral When Service Brake is Depressed and Vehicle is at Stop; Remains in Neutral Until Service Brake is Released

TRANSMISSION TCM LOCATION Located Inside Cab

SHIFT CONTROL PARAMETERS (Allison) 3000 or 4000 Series Transmissions, Performance Programming

PTO LOCATION Customer Intends to Install PTO at Left Side of Transmission

AXLE, REAR, SINGLE (Meritor RS-23-160) Single Reduction, 23,000-lb Capacity, 200 Wheel Ends. Gear Ratio: 4.89

SUSPENSION, REAR, SINGLE 23,500-lb Capacity, Vari-Rate Springs, with 4500-lb Capacity Auxiliary Rubber Springs

FUEL/WATER SEPARATOR {Racor 400 Series,} 12 VDC Electric Heater, Includes Pre-Heater, with Primer Pump, Includes Water-in-Fuel Sensor

LOCATION FUEL/WATER SEPARATOR Mounted Under Hood, Left Side, Above Front Axle

FUEL TANK Top Draw, Non-Polished Aluminum, 24" Dia, 50 US Gal (189L), Mounted Left Side, Under Cab

DEF TANK 5 US Gal (19L) Capacity, Frame Mounted Outside Left Rail, Under Cab

AUXILIARY FUEL DRAW TUBE Located at Auxiliary Port on Fuel Tank

CAB Conventional, Day Cab

AIR CONDITIONER with Integral Heater and Defroster

GAUGE CLUSTER Base Level; English with English Electronic Speedometer

GAUGE, TEMPERATURE, AMBIENT Sensor Wiring with Display Unit Mounted in Cluster

GAUGE, OIL TEMP, AUTO TRANS for Allison Transmission

IP CLUSTER DISPLAY On Board Diagnostics Display of Fault Codes in Gauge Cluster

SEAT, DRIVER {National 2000 195} Air Suspension, High Back with Integral Headrest, Vinyl, Isolator, 8" Adjuster, 1 Chamber Lumbar, 2 Position Front Cushion Adjust, 6-23 Degree Angle Back Adjust

GRAB HANDLE, EXTERIOR Chrome, Towel Bar Type, with Anti-Slip Rubber Inserts, for Cab Entry Mounted Left Side at B-Pillar

SEAT, PASSENGER {National} Non Suspension, High Back, Fixed Back, Integral Headrest, Vinyl

MIRRORS (2) Aero Pedestal, Power Adjust, Heated, Black Heads and Arms, 6.5" x 14" Flat Glass, Includes 6.5" x 6" Convex Mirrors, for 102" Load Width

SEAT BELT All Orange; 1 to 3

CAB INTERIOR TRIM Classic, for Day Cab

CAB REAR SUSPENSION Air Suspension, for Mid Cab Height

ARM REST, RIGHT, DRIVER SEAT

WINDOW, MANUAL (2) and Manual Door Locks, Left and Right Doors

**INSTRUMENT PANEL Flat Panel** 

ACCESS, CAB Steel, Driver & Passenger Sides, Two Steps per Door, for use with Day Cab and Extended Cab

WHEEL, SPARE, DISC (Accuride 51408) 22.5x8.25 Rims, Powder Coat Steel, 10-Stud, 285.75mm BC, Hub-Piloted

WHEELS, FRONT (Accuride 51408) DISC; 22.5x8.25 Rims, Powder Coat Steel, 2-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs

## **Description**

WHEELS, REAR {Accuride 51408} DUAL DISC; 22.5x8.25 Rims, Powder Coat Steel, 2-Hand Hole, 10-Stud, 285.75mm BC, Hub-Piloted, Flanged Nut, with Steel Hubs

TIRE, SPARE Equal to Model Standard

BDY INTG, REMOTE POWER MODULE Mounted Inside Cab Behind Driver Seat, Up to 6 Outputs & 6 Inputs, Max 20 amp per Channel, Max 80 amp Total; Includes 1 Switch Pack with Latched Switches

BDY INTG, RPM I/O HARNESS Includes a Harness with Six Input Blunt Cut Wires and Six Output Blunt Cut Wires, for use with one RPM

6

- (3) TIRE, FRONT 11R22.5 Load Range H HSR 3 (CONTINENTAL), 494 rev/mile, 75 MPH, All-Position
- (4) TIRE, REAR 11R22.5 Load Range H HDR2+ (CONTINENTAL), 491 rev/mile, 75 MPH, Drive

## **Services Section:**

WARRANTY Standard for MV Series, Effective with Vehicles Built July 1, 2017 or Later, CTS-2020A

pk MD

Set engine parameters 2025

This proposal is subject to material surcharges, tariffs, and production availability

Pricing is off the current MKCPP contract # 2024-068

## Financial Summary 2026 MV607 SBA (MV607)

September 24, 2025

(US DOLLAR)

<u>Description</u>	<u>Price</u>
Net Sales Price:	\$99,866.00
Approved by Seller:	Accepted by Purchaser:
Official Title and Date	Firm or Business Name
Authorized Signature	Authorized Signature and Date
This proposal is not binding upon the seller without Seller's Authorized Signature	
	Official Title and Date

If you haven't added a planned maintenance service contract to your proposal yet, please get in touch with your local dealer, International or IC Bus Sales Representative to learn more about the benefits when ordering together with the vehicle.

International® Financial offers loans, a full line up of lease options, and can establish a line of credit for use towards the purchase of International and IC Bus vehicles. Ask your dealer, International® or IC Bus® Sales Representative about completing an International Financial credit application and any promotional offers that may be available. International Financial services are provided by Navistar Financial Corporation.

The TOPS FET Calculation is an estimate for reference purposes only. The seller is responsible for calculating and reporting/paying appropriate FET to the IRS.

The limited warranties applicable to the vehicles described here in are International Motors, LLC\* standard printed warranties which are incorporated herein by reference and to which you have been provided a copy and hereby agree to their terms and conditions.

7

International Motors, LLC d/b/a International Motors USA LLC in Illinois and Ohio.